



4K Certification Test Report

Crestron DigitalMedia™ Lab



Report #: _____ Date Test Completed: _____
 Manufacturer: _____ Inputs Tested: _____
 Model: _____ Native Resolution: _____
 Aspect Ratio: _____

EDID structure verification (HDMI® CTS 8-1 through 8-2) . . . Pass **Video protocol compliant** (HDMI CTS 8-17 through 8-20) . . . Pass
TMDS signal integrity (HDMI CTS 8-5 through 8-7) Pass **4K protocol compliant** (HDMI CTS 8-30) Pass

EDID Report

Support as declared by tested device via EDID

DM® Compatible Resolutions

- | | | | | |
|---|---|---|---|---------------------------------|
| <input type="checkbox"/> 640x480@60Hz | <input type="checkbox"/> 1280x960@60Hz | <input type="checkbox"/> 1920x1080@25Hz (1080p25) | <input type="checkbox"/> 3840x2160@24Hz | <input type="checkbox"/> Other: |
| <input type="checkbox"/> 720x480@60Hz (480p) | <input type="checkbox"/> 1280x1024@60Hz | <input type="checkbox"/> 1920x1080@25Hz (1080i25) | <input type="checkbox"/> 3840x2160@25Hz | |
| <input type="checkbox"/> 720x576@50Hz (576p) | <input type="checkbox"/> 1366x768@60Hz | <input type="checkbox"/> 1920x1080@30Hz (1080i30) | <input type="checkbox"/> 3840x2160@30Hz | |
| <input type="checkbox"/> 800x600@60Hz | <input type="checkbox"/> 1400x1050@60Hz | <input type="checkbox"/> 1920x1080@50Hz (1080p50) | <input type="checkbox"/> 3840x2160@50Hz | |
| <input type="checkbox"/> 1024x768@60Hz | <input type="checkbox"/> 1440x900@60Hz | <input type="checkbox"/> 1920x1080@60Hz (1080p60) | <input type="checkbox"/> 3840x2160@60Hz | |
| <input type="checkbox"/> 1280x720@50Hz (720p50) | <input type="checkbox"/> 1600x900@60Hz | <input type="checkbox"/> 1920x1200@60Hz | <input type="checkbox"/> 4096x2160@24Hz | |
| <input type="checkbox"/> 1280x720@60Hz (720p60) | <input type="checkbox"/> 1600x1200@60Hz | <input type="checkbox"/> 2048x1080@60Hz | <input type="checkbox"/> 4096x2160@50Hz | |
| <input type="checkbox"/> 1280x768@60Hz | <input type="checkbox"/> 1680x1050@60Hz | <input type="checkbox"/> 2560x1440@60Hz | <input type="checkbox"/> 4096x2160@60Hz | |
| <input type="checkbox"/> 1280x800@60Hz | <input type="checkbox"/> 1920x1080@24Hz (1080p24) | <input type="checkbox"/> 2560x1600@60Hz | | |

Preferred Timing:

Color Space:

3D:

Audio Formats

- | | | | | | | |
|---|---|---|---------------------------------|--|---|---------------------------------|
| <input type="checkbox"/> No Audio Support | <input type="checkbox"/> Dolby Digital® | <input type="checkbox"/> Dolby Digital Plus | <input type="checkbox"/> DTS® | <input type="checkbox"/> DTS 96/24 | <input type="checkbox"/> DTS-HD Master Audio™ | <input type="checkbox"/> Other: |
| <input type="checkbox"/> Stereo PCM | <input type="checkbox"/> Dolby Digital EX | <input type="checkbox"/> Dolby® TrueHD | <input type="checkbox"/> DTS-ES | <input type="checkbox"/> DTS-HD High Res | <input type="checkbox"/> Up to 8ch PCM | |

CEC Report

Power on (remote control passthru):

Power off (remote control passthru):

Power toggle:

Power on (image view on):

Power off (system standby):

Note: This command turns the display on (if off) and selects the HDMI input from which it received the command (if not already selected.)

Signal Lock Performance

Time to lock on new signal (worst case, in seconds):

Signal lock performance notes:

Other Notes

See how we conduct our 4K certification testing at www.crestron.com/4K

All brand names, product names, and trademarks are the property of their respective owners. Certain trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. ©2014 Crestron Electronics, Inc., Rockleigh, New Jersey

