

TPMC-10

Isys i/O® WiFi Touchpanel

Crestron's incredible Isys i/O TPMC-10 WiFi Touchpanel is a high performance 2-way wireless touchpanel featuring Wi-Fi wireless communications and native capabilities for accessing e-mail, streaming multimedia, and browsing the Internet. A generous 10.4" active-matrix SVGA display and 16-bit color depth combine to produce astounding 3D graphics, dynamic text, full-motion animations, and animated pop-ups.

Embedded PC

The power of Isys i/O is in its embedded PC engine, combining rock solid touchpanel performance with built-in Windows Media® Player, Internet Explorer, and MS Inbox, plus viewers for PowerPoint®, Excel, Word, and Adobe® Acrobat® files. Running the Microsoft® Windows® CE .NET operating system behind the scenes, the TPMC-10 enables Internet access while maintaining secure and reliable touchpanel performance. Programmatic application control erases the lines between control system and PC, allowing programmers to customize each application's behavior to create a truly powerful and user-friendly interface.

Wi-Fi Wireless

Integrated 802.11g Wi-Fi technology with WEP encryption delivers secure, high-speed 2-way wireless performance across existing wireless LAN's, affording total mobile freedom and seamless communications with Crestron control systems, computers, digital media servers, and other IP-based devices.

Advanced Ergonomics

Far more than a mere tablet PC, the TPMC-10 is ingeniously designed to provide a powerful mobile control solution in a compact package that's easy to hold and intuitive to use. The ergonomic shape shifts effortlessly from tabletop to laptop, featuring a sleek contoured base that rests comfortably across one leg. Its smart design achieves an optimal viewing angle under any use, with four programmable hard buttons and



an integrated thumbpad to provide tactile control of audio volume, channel selection, OSM navigation, or even pan/tilt cameras.

For text-intensive applications, two onboard USB ports allow the connection of an external mouse and keyboard (sold separately). A VGA output is also provided to enable display of the touchpanel image on a larger monitor or audience display.

High-Quality Audio

To complement its incredible graphics and computer capabilities, the TPMC-10 delivers great sounding audio from its built-in high-powered tuned-port speaker system. An integrated microphone and stereo headphone output are also provided.

Docking Station Option

Placing the TPMC-10 into the optional **TPMC-10-DS** Docking Station provides a convenient charging solution while simultaneously allowing the touchpanel to be operated in an upright position, with additional USB connectivity provided to support a stationary mouse and keyboard (sold separately).

TPMC-10

Isys i/O® WiFi Touchpanel

SPECIFICATIONS

Touchscreen Display

Display: TFT Active matrix color LCD

Size: 10.4 inch (26.4 cm) diagonal

Aspect Ratio: 4:3 SVGA

Resolution: 800 x 600 pixels

Brightness: 230 nits

Contrast: 500:1

Illumination: Edgelit fluorescent

Viewing Angle: $\pm 60^\circ$ horizontal, $+35/-65^\circ$ vertical @CR>10

Touchscreen: Resistive membrane

Memory

Internal: 64 MB Flash, 128 MB SDRAM;

Operating System

Microsoft® Windows® CE .NET 4.2

Graphic Engine

Isys i/O engine, 16 Bit non-palette graphics, 65,536 colors, Synapse image rendering algorithm

Embedded PC Applications

Microsoft Internet Explorer, Windows Media® Player, MS Inbox and Wordpad, plus viewers for PowerPoint®, Excel, Word, and Adobe® Acrobat®

Wireless Ethernet

RF Transceiver:

IEEE 802.11g Wi-Fi 2.4 GHz 2-way RF 11/13

channels (2400 to 2483 MHz), DHCP/DNS or static IP, 64 and 128-bit WEP encryption, WPA-ready, EAP pass-thru; requires third-party 802.11b/g wireless access point and Ethernet-enabled Crestron 2-Series control system

Range: Up to 328 feet (100m) @54Mbps; transmission speed varies based upon environmental conditions

Video

Formats: WMV, ASX, ASF, MPG, and AVI through Windows Media Player

Audio

Features: Built-in microphone, 10 watt biamplified speakers, stereo headphone output

Formats: WMA, MP3, and WAV through Windows Media Player

Audio Feedback (WAV): 8 & 16 bit PCM, mono & stereo, 8 - 44 kHz sampling rates

Buttons

Function Buttons: (4) "Softkey" buttons, programmable

Thumbpad: (1) 4-way Thumbpad, programmable

Power: (1) Toggles power on/off

Reset: (1) Hard reset button, reboots the touchpanel

LED Indicators

Communication: (1) Indicates wireless signal quality

Power: (1) Indicates power/charging status and battery level

Connectors

VGA OUT: (1) mini-VGA port (DB15HD cable included);

RGBHV (VGA) output;

Aspect ratio: 4:3 SVGA;

MICROPHONE: (1) 3.5 mm TRS mini phone jack (not currently implemented)

HEADPHONES: (1) 3.5 mm TRS mini phone jack

USB: (2) Type A ports for mouse/keyboard and memory devices; (1) Mini B port (not currently implemented)

TPMC-10

Isys i/O® WiFi Touchpanel

PC CARD: (1) Type II PCMCIA Card slot

DC POWER: (1) DC power jack (power supply included)

Power Requirements

Battery: Lithium Polymer 4S1P, 14.8 Volt, 2000 mAh
(included)

Usage per Charge: ~3 hours continuous at full brightness

Charging Time: ~2 hours (~4 hours when in use)

Power Supply/Charger: 60 Watts (3.16 Amps @ 19 Volts DC)
universal 100~240VAC 50/60Hz power supply included

Environmental

Temperature: 50° to 113°F (10° to 45°C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Construction: High impact black/silver injection-molded case with integral 20 degree fixed-tilt base; optimized for tabletop, laptop, and handheld use; stylus storage slot (stylus included); integral docking station port

Dimensions

Height: 2.71 in (6.88 cm)

Width: 11.48 in (29.16 cm)


Depth: 8.38 in (21.29 cm)

Weight

3 lbs (1.36 kg)

TPMC-10

Isys i/O® WiFi Touchpanel



TPMC-10

Isys i/O® WiFi Touchpanel

